



Consolidated Rig Works
6000 E. Berry St., Fort Worth, TX 76119
PH: 817-446-5272 ~ FX: 817-446-4947
E-mail: crwlp@sbcglobal.net
Website: www.crwlp.com

CRW STANDARD SNUBBING EQUIPMENT



150K Jack Specifications:

Jack

- 150,000 lb pulling capacity, 65,000 lb snubbing capacity
- 10' stroke, 3000 psi rated main hydraulic cylinders
- 2 leg-4 leg cylinder operation (4 ball valves)
- Husco split spool valve package with regeneration circuit
- Main frame designed for using CRW HC slip bowls
- 7.06" through bore
- 7.06" stripper bowl with adapters

Slip Bowls (CRW 3.5"/150K High Capacity)

- 150,000 lbs maximum load capacity
- Hydraulic cylinder actuated
- Built in compliance with API-8C (with exceptions)

Work Basket

- Jack operators control panel
- BOP operations control panel
- OSHA compliant handrail height

Rotary

- Max Torque: 3300 ft-lb @ 3000 psi
- Max RPM: 100 RPM @ 270 GPM
- Gear driven
- Oil bath lubrication with integral lube oil pump

Power Pack

- Cummins or Detroit 600 HP engine
- Heavy duty radiator
- Denison pumps
- Skid mounted with protection frame with 4 point lift eyes

Gin Pole

- 14,000 lbs maximum load rating
- 2 section design for lifting single joints
- Hydraulic operated extension winch
- 10,000 lb auxiliary winch

Dual Counterbalance Winch

- Power up, power down operation
- 1,500 lbs. maximum lift capability per winch



Consolidated Rig Works
6000 E. Berry St., Fort Worth, TX 76119
PH: 817-446-5272 ~ FX: 817-446-4947
E-mail: crwlp@sbcglobal.net
Website: www.crwlp.com

CRW STANDARD SNUBBING EQUIPMENT



225K Jack Specifications:

Jack

- 225,000 lb pulling capacity, 120,000 lb snubbing capacity
- 10' stroke, 3000 psi rated main hydraulic cylinders
- 2 leg-4 leg cylinder operation (4 ball valves)
- Husco split spool valve package with regeneration circuit
- Main frame designed for using CRW HC slip bowls
- 11-1/8" through bore
- 11" stripper bowl with adapters

Slip Bowls (CRW 5.5"/225K Full Open High Capacity)

- 225,000 lbs maximum load capacity
- Hydraulic cylinder actuated
- Built in compliance with API-8C (with exceptions)

Work Basket

- Jack operators control panel
- BOP operations control panel
- OSHA compliant handrail height

Rotary

- 6,600 ft-lb maximum torque at up to 120 rpm
- Gear driven
- Oil lubrication with integral lube oil pump

Power Pack

- Cummins or Detroit 600 HP engine
- Heavy duty radiator
- Denison pumps
- Skid mounted with protection frame with 4 point lift eyes

Gin Pole

- 14,000 lbs maximum load rating
- 2 section design for lifting single joints
- Hydraulic operated extension winch
- 10,000 lb auxiliary winch

Dual Counterbalance Winch

- Power up, power down operation
- 1,500 lbs. maximum lift capability per winch



Consolidated Rig Works
6000 E. Berry St., Fort Worth, TX 76119
PH: 817-446-5272 ~ FX: 817-446-4947
E-mail: crwlp@sbcglobal.net
Website: www.crwlp.com

CRW STANDARD SNUBBING EQUIPMENT



285K Jack Specifications:

Jack

- 285,000 lb pulling capacity, 170,000 lb snubbing capacity
- 11-1/2' stroke, 3000 psi rated main hydraulic cylinders
- 2 leg-4 leg cylinder operation (4 ball valves)
- Husco split spool valve package with regeneration circuit
- Main frame designed for using CRW FB slip bowls
- 7.06" through bore

Slip Bowls (CRW 7-1/16"/300K Full Bore)

- 300,000 lbs maximum load capacity
- Hydraulic cylinder actuated
- Built in compliance with API-8C (with exceptions)

Work Basket

- Jack operators control panel
- BOP operations control panel
- OSHA compliant handrail height

Rotary

- 10,000 ft-lb maximum torque at up to 108 rpm
- Gear driven
- Oil lubrication with integral lube oil pump

Power Pack

- Fully enclosed
- Weather resistant
- Minimum 500 BHP
- Heavy duty radiator
- Denison pumps
- Standard 4-point lifting sling

Gin Pole

- 14,000 lbs maximum load rating
- 2 section design for lifting single joints
- Hydraulic operated extension winch

Dual Counterbalance Winch

- Power up, power down operation
- 1,500 lbs. maximum lift capability per winch



Consolidated Rig Works
6000 E. Berry St., Fort Worth, TX 76119
PH: 817-446-5272 ~ FX: 817-446-4947
E-mail: crwlp@sbcglobal.net
Website: www.crwlp.com

CRW STANDARD SNUBBING EQUIPMENT



340K Jack Specifications:

Jack

- 340,000 lb pulling capacity, 190,000 lb snubbing capacity
- 10' stroke, 3000 psi rated main hydraulic cylinders
- 2 leg-4 leg cylinder operation (4 ball valves)
- Husco split spool valve package with regeneration circuit
- Main frame designed for using CRW HC slip bowls
- 11-1/8" through bore
- 11" stripper bowl with adapters

Slip Bowls (CRW 7.63"/340K High Capacity)

- 340,000 lbs maximum load capacity
- Hydraulic cylinder actuated
- Built in compliance with API-8C (with exceptions)

Work Basket

- Jack operators control panel
- BOP operations control panel
- OSHA compliant handrail height

Rotary

- Max Torque: 10000 ft-lb @ 3000 psi
- Max RPM: 100 RPM @ 270 GPM
- Gear Drive
- Plumbed with 2 selector valves for selecting 2, 3, or 4-motor operation

Power Pack

- Cummins or Detroit 600 HP engine
- Heavy duty radiator
- Denison pumps
- Skid mounted with protection frame with 4 point lift eyes

Gin Pole

- 14,000 lbs maximum load rating
- 2 section design for lifting single joints
- Hydraulic operated extension winch
- 10,000 lb auxiliary winch

Dual Counterbalance Winch

- Power up, power down operation
- 1,500 lbs. maximum lift capability per winch



Consolidated Rig Works
6000 E. Berry St., Fort Worth, TX 76119
PH: 817-446-5272 ~ FX: 817-446-4947
E-mail: crwlp@sbcglobal.net
Website: www.crwlp.com

CRW STANDARD SNUBBING EQUIPMENT



460K Jack Specifications:

Jack

- 460,000 lb pulling capacity, 226,000 lb snubbing capacity
- 10' stroke, 3000 psi rated main hydraulic cylinders
- 2 leg-4 leg cylinder operation (4 ball valves)
- Husco split spool valve package with regeneration circuit
- Main frame designed for using CRW HC slip bowls
- 13.75" through bore
- 11" stripper bowl with adapters

Slip Bowls (CRW 7.63"/600K High Capacity)

- 600,000 lbs maximum load capacity
- Hydraulic cylinder actuated
- Built in compliance with API-8C (with exceptions)

Work Basket

- Jack operators control panel
- BOP operations control panel
- OSHA compliant handrail height

Rotary

- Max Torque: 12000 ft-lb @ 3000 psi (3-motor), 16000 ft-lb @ 3000psi (4-motor)
- Max RPM: 50 RPM @ 140 GPM
- Gear Drive
- Plumbed with selector valve for selecting 3- or 4-motor operation

Power Pack

- Cummins or Detroit 600 HP engine
- Heavy duty radiator
- Denison pumps
- Skid mounted with protection frame with 4 point lift eyes

Gin Pole

- 14,000 lbs maximum load rating
- 2 section design for lifting single joints
- Hydraulic operated extension winch
- 10,000 lb auxiliary winch

Dual Counterbalance Winch

- Power up, power down operation
- 1,500 lbs. maximum lift capability per winch